




9.7" Industrial HMI




- 1024 x 768 Pixel Resolution
- Ethernet
- 2 Serial Ports
- 1 USB Host Port

System	CPU	32-bit RISC Cortex-A8, 1 GHz
	Memory (RAM)	256 MB
	Memory (Flash)	512 MB
	RTC	Built-in
I/O Ports	Serial	1 x DE9P COM1: RS-232 1 x DE9S COM2: RS-485 2 or 4 wire, COM3: RS-485 2 wire
	Ethernet	1 x 10/100 Base-T
	CANbus	N/A
	USB Host	1 x USB 2.0
	USB Client	N/A
	Audio	N/A
	Video	N/A
	Wi-Fi	N/A
	HDMI	N/A
	SD Card Slot	N/A
Display	Display Type	9.7" TFT LCD
	Size (W x H)	7.78 x 5.83 inches [197 x 148 mm]
	Resolution (pixels)	1024 x 768
	Luminance (cd/m²)	350
	Contrast Ratio	500:1
	Max. Colors	262 K
	Backlight Lifetime (hours)	30,000+
Touch Screen	Type	4-wire resistive touch
	Active Area Accuracy	Length (X) ± 2%, width (Y) ± 2%
Electrical	Input Voltage	24 ± 20% VDC
	Input Current	500 mA @ 24 VDC
	Power Isolation	Built-in
	Isolation Resistance	Exceed 50 MΩ at 500 VDC
Mechanical	Enclosure	Plastic, charcoal grey/silver
	PCB Coating	Yes
	Dimensions (W x H x D)	10.26 x 8.00 x 1.44 inches [261 x 203 x 37 mm]
	Weight	1.87 lbs. [0.85 kg]
	Mounting	Panel or VESA 75 x 75 mm mounting
Environmental	Operating Temperature	32° ~ 122° F (0° ~ 50° C)
	Storage Temperature	-4° ~ 140° F (-20° ~ 60° C)
	Relative Humidity	10% ~ 90% (non-condensing)
	Vibration Endurance	10 to 25 Hz (X, Y, Z direction, 2 G, 30 minutes)
	Ratings	IP65 compliant front panel, NEMA 4X indoor use only
	Certifications	CE, RoHS
Software	EZwarePlus (v4.00.01 or later)	
Notes		


Top View




Front View




Side View




Rear View



Cutout Dimensions



Bottom View



Dimensions are in inches [mm]

- Ⓐ Fuse
- Ⓑ VESA Mounts
- Ⓒ Ethernet Port
- Ⓓ USB 2.0 Host Port
- Ⓔ Com Port DE9P
- Ⓕ Com Port DE9S
- Ⓖ Power Connector