




## 4.3" Touchscreen HMI



- Security, Datalogging
- Trends, Plots
- Pass through mode
- Macros
- Serial & Ethernet


EasyAccess20

<b>System</b>	<b>CPU</b>	32-bit RISC Cortex-A8, 600 MHz
	<b>Memory (RAM)</b>	128 MB
	<b>Memory (Flash)</b>	128 MB
	<b>RTC</b>	Built-in
<b>I/O Ports</b>	<b>Serial</b>	1 x DE9P COM1: RS-232/RS-485 2 or 4 wire, COM 3: RS-485 2 wire
	<b>LAN</b>	1 x 10/100 Base-T
	<b>CANbus</b>	N/A
	<b>USB Host</b>	1 x USB 2.0
	<b>USB Client</b>	N/A
	<b>Audio</b>	N/A
	<b>Video</b>	N/A
	<b>Wi-Fi</b>	N/A
	<b>HDMI®</b>	N/A
	<b>SD Card Slot</b>	N/A
<b>Display</b>	<b>Display Type</b>	4.3" TFT LCD
	<b>Size (W x H)</b>	3.74 x 2.13 inches [95 x 54 mm]
	<b>Resolution (pixels)</b>	480 x 272
	<b>Max. Colors</b>	16.7 M
	<b>Luminance (cd/m²)</b>	400
	<b>Viewing Angle (H°/V°)</b>	140/120
	<b>Contrast Ratio</b>	500:1
<b>Backlight Lifetime (hours)</b>	30,000+	
<b>Touch Screen</b>	<b>Type</b>	4-wire resistive touch
	<b>Active Area Accuracy</b>	Length (X) ±2%, width (Y) ±2%
<b>Electrical</b>	<b>Input Voltage</b>	10.5 ~ 28 VDC
	<b>Input Current</b>	800 mA @ 12 VDC, 400 mA @ 24 VDC
	<b>Input Power</b>	9.6 W
	<b>Power Isolation</b>	Built-in
	<b>Isolation Resistance</b>	Exceed 50 MΩ at 500 VDC
<b>Mechanical</b>	<b>Enclosure</b>	Plastic, charcoal grey
	<b>PCB Coating</b>	N/A
	<b>Dimensions (W x H x D)</b>	5.04 x 4.02 x 1.26 inches [128 x 102 x 32 mm]
	<b>Net Weight</b>	Approx. 0.55 lbs. [0.25 kg]
<b>Environmental</b>	<b>Mounting</b>	Panel mounting
	<b>Operating Temperature</b>	32° ~ 122°F (0° ~ 50°C)
	<b>Storage Temperature</b>	-4° ~ 140°F (-20° ~ 60°C)
	<b>Relative Humidity</b>	10% ~ 90% (non-condensing)
	<b>Vibration Endurance</b>	10 to 25 Hz (X, Y, Z direction, 2G, 30 minutes)
	<b>Ratings</b>	NEMA 4, IP65 compliant front panel
<b>Software</b>	<b>Certifications</b>	CE, RoHS
	<b>Software</b>	EBPro (v6.00.01.174 or later), Modbus, VNC Server
<b>Notes</b>	Specifications subject to change without notice	




Top View


Dimensions are in inches [mm]




Front View




Side View



Cutout Dimensions



Rear View



Bottom View

- A Power Connector
- B COM Port DE9P
- C USB 2.0 Host Port
- D Ethernet Port